

FULLY AUTOMATIC (Tilting Back-Arm)

Tyre Changer



**MOTOREX
HOIST**

Since 2005

Fully-automatic tyre changer with advanced configure. Push-pull horizontal arm, tilt back vertical arm, equipped with assistant inflating device and helper make the operation time saving, safe and easy. Highly suitable for wide, low-profile, stiff and tubeless tyres. Great for large tyre repair shop.

AA-TC-188

CE approved

- Hexangular shaft, used S41mm steel, not easy to distort, ensure the operation of low-profile and stiff tyre more safety.
- The turntable, use $\delta 15$ mm steel, the surface of the turntable is chrome plated, wearable and anti-septicised.
- Hard wearing alloy material on mounting head.
- This machine equipped with the protection cover for the mounting head, clamps, lever and bead breaker shoe, to avoid the damage for the aluminum alloy rim.
- The inflating system adopt gauge box, equipped with rubber inflating hose, ensure durability and safety.
- This machine with "C" configure, "C" means tubeless tyre inflating device, make the edge of the tubeless tyre connect tightly with the rim, to avoid the leakage when inflating.
- Full-automatic tyre changer with push-pull horizontal arm and tilt back vertical arm, pneumatic locking for work efficiency.
- CE approved**



**TRUSTED
VEHICLE LIFT
SOLUTION
PROVIDER**

[SALES |
INSTALLATION |
PARTS & SERVICE]

MOTOREX * PRICE *

GST inclusive

Technical Parameters

| | |
|----------------------------------|------------------------|
| Motor power | 1.1kw |
| Power supply | 220v 240v 1PH/3PH |
| Operation pressure | 8-10 bar |
| Max. wheel dia | 44" (1120 mm) |
| Max. wheel width | 14" (360 mm) |
| Rim clamping from outside | 10" -21" |
| Rim clamping from inside | 12" -24" |
| Bead-breaker force | 2500 kg |
| Noise | <70 dB |



**NATIONWIDE
DELIVERY**

**NZ
OWNED**
Since 2005

www.motorexhoist.com

CALL: 021-2627162

